

ACCIONADOR ELECTROMECHANICO PARA PUERTAS DE HASTA 400 kg

DOLFIN

24Vdc



_ Transmisión a correa.



DOLFIN KITS

DOLFIN 3

Accionador DOS424E (1 u.)
Guía de aluminio 4 mts ADO02 (1 u.)
Receptor R RSD (1 u.)
Emisor LU02 (1 u.)
Fotocélula LECP (1 u.)

DOLFIN 4

Accionador DOS424E (1 u.)
Guía de aluminio 6 mts ADO02 (1 u.)
Receptor R RSD (1 u.)
Emisor LU02 (1 u.)
Fotocélula LECP (1 u.)



KIT DOLFIN 3



DOS424E
1 u.

ADO02
1 u.



LU02
1 u.



R RSD
1 u.



LECP
1 u.

CARACTERÍSTICAS TÉCNICAS

	DOS424E
Alimentación (V/Hz)	230 V/50
Potencia consumida (W)	400
Tensión motor (Vdc)	24
Grado de protección (IP)	44
Par máximo (Nm)	15
Temperatura de servicio (°C)	-20 / +55
Peso (kg)	6,5
Máx. peso puerta (kg)	400
Uso (ciclos/hora)	30
Velocidad máxima (m/min)	13

